



Main

Product or component type	Fan controller
Provided equipment	Capacitor Screws Switch Grid plate Skin
Colour	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 10
Sale per indivisible quantity	1

Complementary

Switch function	4 positions
Control type	Rotary
Number of rocker	1
Actuator	Rotary
Product destination	Ceiling fan
Marking	0 - 1 - 2 - 3
Surface finish	Matt
Surface treatment	Untreated
Ambient air temperature for storage	0...60 °C
Load type	Fan Motor
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	20000 cycles, conforming to AS/NZS 60669
Connections - terminals	4 x screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1.5 mm ² (stranded) 1.5 mm ² (flexible) 1.5 mm ² (rigid)
Wire stripping length	10 mm
Material	Skin : PC (polycarbonate) Skin : ABS (acrylonitrile butadiene-styrene) Grid plate : PC (polycarbonate) Flaps : PP (polypropylene) Housing : PC (polycarbonate) Housing : PA66 Locking bar : POM (polyoxymethylene)
Height	120 mm
Width	78 mm
Depth	49 mm
Product weight	0.104 kg

Environment

Product certifications	RCM
------------------------	-----

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.