



### Main

Range of product	Clipsal Iconic
Product or component type	Switch mechanism
Device presentation	Mechanism
Provided equipment	Switch Knob Carrier labelled with switch position
Device application	Lighting
Fixing mode	Locking bar
Colour	Vivid white (VW) Anthracite (AN) Cool grey (CY) Warm grey (WY)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Rated current	10 A - 250 V AC, 50 Hz

### Complementary

Switch function	4 positions
Control type	Rotary
Actuator	Rotary
Marking	0 - 1 - 0 - 2
Surface finish	Matt
Surface treatment	Untreated
Ambient air temperature for storage	0...60 °C
Motor M-rating AS3133	M40
Load type	Inductive Motor
Dielectric strength	20000 V
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	20000 cycles, conforming to AS/NZS 60669
Connections - terminals	4 x screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	1.5 mm <sup>2</sup> (stranded) 1.5 mm <sup>2</sup> (flexible) 1.5 mm <sup>2</sup> (rigid)
Wire stripping length	10 mm
Material	Housing : PC (polycarbonate) Housing : PA66 Knob : PC (polycarbonate) Knob cap : ABS (acrylonitrile butadiene-styrene)
Height	23 mm
Width	23 mm
Depth	50 mm
Product weight	0.02 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

---

Product certifications

RCM

---