

C-Bus PC Interface



5500PC

The DIN rail mounted C-Bus PC Interface (or C-Bus PCI) is a C-Bus system device designed to provide a gateway between a PC and a C-Bus Network.

Through the C-Bus PC interface, C-Bus Units can be programmed, commands can be issued to the C-Bus Network and activity on the C-Bus Network can be monitored.

The C-Bus PC Interface uses a standard RS232 serial port connection and allows an external device with RS232 output to be interfaced to a C-Bus system.

Clipsal Integrated Systems offers a PCI Development Kit (5000DK) which enables third party developers to integrate their systems with C-Bus.

The PC Interface can be programmed to generate the C-Bus system clock for communications data synchronisation on the C-Bus Network and also provides a software selectable Network Burden.

Installation of the C-Bus PC Interface on the C-Bus Network requires connection to the Category 5 unshielded twisted pair C-Bus Network Cable. The connection to a personal computer is via the on-board 9-pin D type serial connector or 8 pin RJ45 connector.

The unit incorporates C-Bus and Unit/Communications LED indicators. These LED's indicate if the unit is powered and functional, if sufficient C-Bus Network voltage is available, if a valid C-Bus clock signal is present and if data transfer is currently taking place.

Like all the other units that make up a C-Bus system, the DIN rail C-Bus PC Interface is Australian designed, developed and manufactured by Clipsal Integrated Systems Pty Ltd.

clipsal.com/cis

5500PC C-Bus PC Interface

- Provides a gateway between a PC and a C-Bus Network.
- Provides an RS-232 interface into a C-Bus Network for control and monitoring via a 3rd party device. Contact Clipsal Integrated Systems for more information.
- DIN Rail mounted.
- 4 DIN modules wide.
- Requires connection to a C-Bus Network via an unshielded twisted pair C-Bus Network Cable.
- 2 x RJ45 sockets provided for C-Bus connections.
- Connection to a personal computer via a 9-pin D type serial connector or an 8-pin RJ45 connector.
- Capable of generating a C-Bus system clock for communications data synchronization.
- Provides a software selectable Network Burden.
- Consumes 32mA from the C-Bus Network.
- Incorporates a Unit/Communications LED Indicator.
- Incorporates a C-Bus LED Indicator.
- A data cable with a DB9 socket and a DB9 plug is supplied with the PC Interface.
- Dimensions: H=85mm, W=72mm, D=65mm
- Weight 104g.



Head Office

12 Park Terrace, Bowden, South Australia 5007
Telephone (08) 8269 0560
International +61 8 8269 0560
Facsimile (08) 8346 0845
International +61 8 8346 0845
E-Mail cis@clipsal.com.au
Internet clipsal.com/cis

International Enquiries

Head Office Export Department

Telephone +61 8 8269 0587
Facsimile +61 8 8340 7350
E-Mail export@clipsal.com.au
Internet clipsal.com

New Zealand

Clipsal Industries (NZ) Ltd
Telephone +64 9 576 303

Malaysia

Clipsal Integrated Systems (M) Sbn Bhd
Telephone +60 3 7665 3555

Singapore

CIS Pte Ltd (Singapore)
Telephone +65 266 1998

Hong Kong

Clipsal Integrated Systems (HK) Limited
Telephone +852 2 487 0261

China

Clipsal China Limited
Telephone +86 755 246 1122

Taiwan

Clipsal (Taiwan) Co Ltd
Telephone +886 2 25583456

Thailand

Clipsal Thailand Ltd
Telephone +66 2 952 5338

South Africa

Clipsal South Africa (Pty) Ltd
Telephone +27 11 314 5200

United Kingdom

Clipsal Ltd (UK)
Telephone +44 1494 521 111

Greece

Clipsal Hellas S.A.
Telephone +30 1 993 9165

