

Move forward to big things.
Clipsal Avanti.

AVANTI

Clipsal have really covered all bases with the introduction of the new C-Bus Avanti Switch Range. Clipsal's Avanti Switches are C-Bus programmable and incorporate a unique 'long throw' switch action.

The unique 'long throw' design and large switch mechanism is far easier to operate compared to conventional wall switches due to its light touch operation and smooth action. The Clipsal Avanti Range has a low profile architectural look and is ideal for aged care, disabled and commercial applications, including residential homes.

Features and benefits include:

- Large, smooth action switches that are easy to operate
- 1, 2 or 3 gang configuration
- Coloured LED's for load status
- C-Bus programmable.



Installer Benefits

- Standard pattern wall mounting (horizontal configuration only)
- Learn mode capabilities
- Programmable Scenes
- Configurable LED status indication.

User Benefits

- Large rocker switch for aged care or disabled applications
- Coloured LED load status indicators
- 1,2 or 3 gang configuration.

Specifications

Parameter	Description		
C-Bus voltage	15 to 36V DC, 18mA for normal operation. Does not provide current to C-Bus network.		
C-Bus AC input impedance	3.75kV RMS from C-Bus to mains (provided externally to 509xNL series unit)		
Maximum number of units per network	100		
Control functions	Load switching, dimming, timers and scene control		
Status indicators	User configurable red and green		
Warm-up time	5 seconds		
C-Bus connection	One terminal block to accommodate 0.2 to 1.3mm ² (24 to 16 AWG)		
Operating temperature range	0 to 45° C		
Operating humidity range	10 to 95% Relative humidity		
Dimensions (W x H x D)	121 x 82 x 29mm		
Protrusion from wall	13mm		
Mounting centres	84mm		
Weight	5091NL	5092NL	5093NL
	87g	89g	91g

Product range

1 Button, C-Bus Large Rocker Switch	5091NL, WE
2 Button, C-Bus Large Rocker Switch	5092NL, WE
3 Button, C-Bus Large Rocker Switch	5093NL, WE



Product of Clipsal Australia Pty Ltd

A member of the Schneider Electric Group

Head Office

12 Park Terrace, Bowden
South Australia 5007

Telephone (08) 8269 0511

Facsimile (08) 8340 1724

Internet clipsal.com

E-Mail plugin@clipsal.com.au

National Customer Service Enquiries:

1300 2025 25

National Customer Service Facsimile:

1300 2025 56

International Enquiries

International Sales and Marketing

Telephone + 61 8 8269 0587

Facsimile + 61 8 8340 7350

E-Mail export@clipsal.com.au

New Zealand

Clipsal Industries (NZ) Ltd

Telephone (09) 576 3403

Facsimile (09) 576 1015

E-Mail headoffice@clipsal.co.nz

Customer Service

Free Fax (0508) 250 305

Auckland/Mobile Phone (09) 572 0014

Free Phone (0508) CLIPSAL

2 5 4 7 7 2 5

You can find this brochure and many others online in PDF format at: clipsal.com

Follow the links off the home page or access the following page directly:

clipsal.com/wat_lib_pdf.cfm

clipsal.com

Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© Clipsal Australia Pty Ltd.